



kramer

RTBUS-25xl

Round Table Mount Multi-Connection
Solution – Pneumatic Lid

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



The RTBUS-25xl is an elegant furniture-mounted, modular, round connection bus featuring a pneumatic mechanism for pneumatic lifting and smooth closing of its lid. It is easily installed into a table or podium top and its interface enables you to connect any equipment to systems installed in a room via pass-through connectors for PC, USB, stereo audio, HDMI, Ethernet and power.

NOTE: The power socket and power cord are purchased separately

FEATURES

Inputs - 15-pin HD, USB, 3.5mm, HDMI, Ethernet

Cover - Pop-up pneumatic lid

Cutout Size (Mount Dimension) - 111-114mm diameter



kramer

TECHNICAL SPECIFICATIONS

| | |
|--------------------------|--|
| Ports | 1 HDMI: On a female HDMI connector 1 VGA: On a 15-pin d-sub connector 1 Audio: On a 3.5mm mini jack 1 Ethernet: On an RJ-45 connector 1 USB: On a female USB type-A connector |
| PHYSICAL | Cutout Size 111–114mm diameter |
| Environmental Conditions | Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: –40° to +70°C (–40° to 158°F) Humidity: 10% to 90%, RHL non-condensing |
| Power | Power rating varies according to the location and the power socket assembly (purchased separately) installed in the tbus, as follows: Universal: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet USA: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet Germany and EU: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet Belgium and France: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet Italy: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet Australia: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet Israel: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet South Africa: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet Switzerland: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet England: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet Brazil: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet Fuse Rating: T 6.3A 250V |
| Accessories | Included: Mounting brackets Optional: TBUS AC Power Cord, power socket kits |
| Product Dimensions | 15.70cm x 12.80cm x 15.35cm (6.18" x 5.04" x 6.04") W, D, H |
| Product Weight | 0.9kg (1.9lbs) approx |
| Shipping Dimensions | 36.50cm x 17.00cm x 17.00cm (14.37" x 6.69" x 6.69") W, D, H |
| Shipping Weight | 1.2kg (2.6lbs) approx |

