



kramer

TP-590T

4K60 4:2:0 HDMI Transmitter with USB, RS-232, & IR over Long-Reach HDBaseT 2.0

| HDMI | HDBaseT | 4K/60 UHD (4:2:0)



TP-590T is a high-performance, long-reach HDBaseT 2.0 transmitter for 4K60Hz (4:2:0) HDMI, USB, RS-232, and IR signals over twisted pair. TP-590T converts all input signals into the transmitted HDBaseT 2.0 signal. It extends video signals to up 40m (130ft) over CAT copper cables at up to 4K@60Hz (4:2:0) 24bpp video resolution and provides even further reach for lower HD video resolutions

FEATURES

High Performance Standard Extender - Professional HDBaseT extender for providing long-reach signals over twisted-pair copper infrastructures. TP-590T is a standard extender that can be connected to any market-available HDBaseT-compliant extension product. For optimum extension reach and performance, use recommended Kramer cables

HDMI Signal Extension - HDCP 2.3, EDID and CEC signals are passed through from the source to the display. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0

Flexible USB 2.0 Extension - An active USB host is connected at either the transmitter or receiver side. USB 2.0 signals are extended between the transmitter and receiver, enabling connection of the active USB host to both local and remote USB devices, such as camera and audio devices, or HID (Human Interface Devices) mouse or keyboard devices

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling, processing, and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems

Multi-channel Audio Transmission - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

Bidirectional RS-232 Extension - Serial interface data flows in both directions, allowing data transmission and device control

Bidirectional Infrared Extension - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line

Cost-effective Maintenance - Status LED indicators for HDMI, HDBT, and USB active host ports, facilitate easy local maintenance and troubleshooting

Easy and Elegant Installation - Compact DemiTOOLS™ fan-less enclosure for dropped-ceiling mounting, or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter



kramer

TECHNICAL SPECIFICATIONS

Inputs	1 HDMI: On an HDMI connector
Outputs	1 HDBT: On an RJ-45 female connector
Ports	1 USB 2.0 Host: On a USB-B connector 3 USB 2.0 Device: On USB type-A connectors 1 IR: On a 3.5mm mini jack for IR link extension, 1 RS-232: On a 3-pin terminal block for serial link extension
USB Features	Integrated USB Hubs 1
Extension Line	Up to 40m (130ft): At 4K @60Hz (4:2:0): Up to 70m (230ft): At full HD (1080p @60Hz 36bpp) Note: When using Kramer HDBaseT cables Standards Compliance: HDBaseT 2.0
Video	Max Data Rate: 10.2Gbps bandwidth (3.4Gbps per graphic channel) Max Resolution: 4K UHD @60Hz (4:2:0) 24bpp resolution Content Protection: HDCP 2.3 HDMI Support: 4K as specified in HDMI 2.0
Extended USB	Host Compliance: 1.1 and 2.0 Extended Line Rate Bandwidth: Up to 127Mbps (out of max 480 USB)
Extended RS-232	Baud Rate: 300 to 115200
Power	Source: 5V DC, 4A Consumption: 3.2A USB Device Charging Max Total Current: 2A
Enclosure	Size: DemiTools Type: Aluminum Cooling: Convection ventilation
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing Vibration: ISTA 1A in carton (International Safe Transit Association)
Regulatory Compliance (Standards Compliance)	Safety: CE Environmental: RoHs and WEEE ACCESSORIES:

Accessories Included: Power adapter, bracket, rubber feet

Product Dimensions 19.05cm x 5.96cm x 2.74cm (7.50" x 2.35" x 1.08") W, D, H

Product Weight 0.5kg (1.1lbs) approx

Shipping Dimensions 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

Shipping Weight 1.0kg (2.2lbs) approx

