

PRO MIXER DJX900USB

Professional 5-Channel DJ Mixer with infinium "Contact-Free" VCA Crossfader, Advanced Digital Effects and USB/Audio Interface

- Professional 5-channel ultra-low noise DJ mixer with stylish, black design
- 45-mm infinium "contact-free" optical crossfader with adjustable tension and fader curve for years of use
- State-of-the-art 24-bit digital effects with advanced parameter control
- Built-in USB interface for recording and playback of any digital music file. Works with your PC or Mac computer—no setup or drivers required
- Intelligent dual auto-BPM counter with time and beat sync display
- 3-band kill EQ and precise level meters with peak hold function per channel
- Additional 3-way kill switches with extremely steep frequency separation
- Awesome adjustable XPQ stereo surround effect
- VCA-controlled faders for utmost reliability and noise-free performance
- Adjustable crossfader curve for all mixing styles



What do you get when you merge the highly successful PRO MIXER DJX750 with the super-smooth infinium "contact-free" optical crossfader and built-in USB connectivity? You get the DJ mixer that's sure to set a new industry standard—the BEHRINGER DJX900USB.

Contact-free infinium crossfader

The DJX900USB features our super-smooth channel faders and the infinium "contact-free" VCA-controlled optical crossfader for the ultimate in reliability and state-of-the-art audio performance. A dedicated CF Curve control allows you to custom-tailor the crossfader's control characteristic, and you can even set the crossfader tension just the way you like it.

Special FX

When we began design on the DJX900USB, we knew we had to do something very special. We took our best analog DJ mixer and revved up the FX processor, putting advanced parameter control right at your fingertips. No longer confined to rigid presets that limit creativity, you can change FX parameters on-the-fly, pushing your performance to the next level. In no time you can create powerful sets with your own custom-tailored effects sounds, all of which can be controlled in real-time. We also included a professional USB audio interface, so you can play tracks directly from your PC/Mac computer or an external thumb drive.

Continued on next page



PRO MIXER DJX900USB

- Monitor function with master/cue balance control and split option
- Auto-talkover function with separate depth control
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

Features galore

Because your voice is your instrument, the DJX900USB features a dedicated mic channel with a built-in Talkover function that automatically detects your voice and brings down the volume of the music track (referred to as “ducking”), so your voice is always out front. Vocal fine-tuning is handled by the onboard 3-band EQ, which provides up to 15 dB of boost or cut at Low (80 Hz), Mid (2.5 k), and High (12 kHz) frequency centers—for an extremely broad tonal palette. Equipped to handle any conceivable input source, these channels accept everything from line level, phono, CD and tape decks to MP3 and minidisk players.

Dual Auto BPM Counters


Sync'ing up tracks is an art unto itself—that's why we gave the DJX900USB dual Auto BPM Counters. This cool feature helps take the guesswork out of making a smooth transition from one track to the next. Each BPM counter's digital display shows which channel it is tracking and the

tempo of the music in beats per minute. Optionally, you can push the Beat Assist button in time with the song to manually enter the tempo. You get a read out of the tempo difference between the tracks, as well as a visual confirmation when they are in sync. These tools will help you seamlessly align two tracks—without having to rely solely on your ears.

Master of illusions

Making music sound larger than life is what it's all about and the DJX900USB comes through on this in a big way. XPQ 3D Surround widens the stereo field, giving it immense depth and a stereo image that is full of life, with amazingly transparent sound. You determine the intensity of this stunning effect with a simple twist of the Surround control—from barely noticeable to supremely spectacular.

Continued on next page



PRO MIXER DJX900USB


Highest quality sound

None of the above-mentioned features would amount to much if the DJX900USB didn't sound truly remarkable. That's why we equip each one with our tried-and-true ULN (Ultra Low-Noise) preamps: what goes in comes out, with nothing added. So you get maximum


headroom, extremely low noise and ultra-transparent sound.

Compare it to the competition for sound quality, features and value and you'll see why more and more DJs are making the move to the new BEHRINGER DJX900USB.

Front Panel



Rear Panel



PRO MIXER DJX900USB

Specifications

Audio Inputs

Mic	+40 dB gain, balanced XLR
Phono in	+40 dB gain, unbalanced
Line in	0 dB gain, unbalanced
CD in	0 dB gain, unbalanced
Return	0 dB gain, unbalanced

Audio Outputs

Master	Max. +21 dBu
Booth	Max. +21 dBu
Tape	0 dBu
Send	0 dBu
Phones out	Max. 180 mW @ 75 Ω / 1% THD

Equalizer

Stereo low	+8 dB/-27 dB @ 50 Hz
Stereo mid	+6 dB/-23 dB @ 1.2 kHz
Stereo high	+9 dB/-15 dB @ 10 kHz
Mic low	+15 dB/-15 dB @ 80 Hz
Mic mid	+15 dB/-15 dB @ 2.5 kHz
Mic high	+15 dB/-15 dB @ 12 kHz
Kill low	-54 dB @ 50 Hz
Kill mid	-43 dB @ 1 kHz
Kill high	-25 dB @ 10 kHz

USB

Audio	Stereo In / Out
Connector	Type B
Sample rate	48 kHz

Digital Effects Processor

DSP	Freescape
A/D-D/A converter	24-bit Delta-Sigma, 64/128-times oversampling

System Specification

Signal-to-noise ratio	> 80 dB (Line)
Crosstalk	> 70 dB (Line)
Distortion (THD)	< 0.03%
Frequency response	10 Hz - 40 kHz, +0/-3 dB

Power Supply

Power consumption	32 W
Mains connection	Standard IEC receptacle

Mains voltages

Europe/UK Australia/Korea/China	220-230 V~, 50/60 Hz
UL	120 V~, 60 Hz
JP	100 V~, 50/60 Hz

Fuse

100-120 V~	T 1 AH 250 V
220-230 V~	T 500 mA 250 V

Physical

Dimensions (H x W x D)	4.2 x 12.6 x 14.6" / 107 x 320 x 370 mm
Weight	8.2 lbs / 3.7 kg

Please note these specifications are preliminary and conceptual in nature, and as such are subject to change as product development progresses. This information is supplied for market research purposes only and is not to be made public in any manner. This document is solely the property of The MUSIC Group, or one of its subsidiaries, and must be surrendered upon request of the owner.

For service, support or more information contact the BEHRINGER location nearest you:

Europe
MUSIC Group Services UK
Tel: +44 156 273 2290
Email: CARE@music-group.com

USA/Canada
MUSIC Group Services NV Inc.
Tel: +1 702 800 8290
Email: CARE@music-group.com

Japan
MUSIC Group Services JP K.K.
Tel.: +81 3 6231 0454
Email: CARE@music-group.com

Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. BEHRINGER is part of the MUSIC Group (music-group.com). All trademarks are the property of their respective owners. MUSIC Group accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. MUSIC Group products are sold through authorized fulfillers and resellers only. Fulfillers and resellers are not agents of MUSIC Group and have absolutely no authority to bind MUSIC Group by any express or implied undertaking or representation. This manual is copyrighted. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of MUSIC Group IP Ltd. ALL RIGHTS RESERVED. © 2012 MUSIC Group IP Ltd. Trident Chambers, Wickhams Cay, P.O. Box 146, Road Town, Tortola, British Virgin Islands. 985-10000-00490