

110 Ω balanced

OT2000

OmniTRANS - Mobile AES/EBU Audio Cable - n x 2 x 0.22 mm²

- high-flexible
- robust jacket (Ø 6.5 mm)



PVC

The usage of cables in theatres and on stages often requires contradictory specifications to the lines used. Flexibility and at the same time robustness in relation to extremely high mechanical stress are needed. These are realised with the OT2000 by cotton filling threads in the interstices, which provide for a stable pair twisting, needed for repeated winding and unwinding, a very close spiral screen and a very thick outer jacket from soft PVC rounds off the cables characteristics.

	Conductor	stranded tinned copper, 7 x 0.20 mm (AWG 24/7)	
	Cross Section	0.22 mm ²	
	Insulation	Foam-Skin PE	
	Core Arrangement	2 cores twisted to a pair	
	Shielding	tinned copper spiral shield , 95%	
	Overall Jacket	PVC, matt	
	Overall Diameter	6.5 mm	
	Min. Bending Radius	35 mm	
	Working Temperature	-20 °C / +70 °C	
	Conductor Resistance	80 Ω/km	
	Shield Resistance	30 Ω/km	
	Capacitance	52 pF/m	
	Characteristic Impedance	110 Ω	
	Attenuation [dB/100m]		
1 MHz	2.1	1 MHz	2.1
3 MHz	5.2	3 MHz	5.2
10 MHz	12.5	10 MHz	12.5
	Insulation Resistance	> 10 GΩ x km	
	Test Voltage		
Cond./Cond.	1200 V	Prüfspannung	
Cond./Shield	500 V	Ader/Ader	1200 V
		Ader/Schirm	500 V

■ black

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length [m] Standard Längen [m]	Max. Length / Reel Max. Länge / Spule
OT2000	black	50 g/m	100 / 500	2500 m

Der Einsatz in Theatern und auf Bühnen erfordert oft widersprüchliche Anforderungen an die dabei eingesetzten Leitungen. Flexibilität und gleichzeitig Robustheit gegenüber äußerst hohen mechanischen Beanspruchungen. Realisiert werden diese beim OT2000 durch Baumwollfüllfäden in den Paarwickeln, die für eine stabile Paarverseilung beim wiederholten Auf- und Abtrommeln sorgen, einen flexiblen Wendelschirm und einen sehr dicken Außenmantel aus

Leiteraufbau	verzinnte Cu-Litze, 7 x 0,20 mm (AWG 24/7)
Leiterquerschnitt	0,22 mm ²
Isolation	Foam-Skin PE
Aderanordnung	2 Adern zum Paar versiebt
Abschirmung	verzinnerter Cu-Wendelschirm, 95%
Außenmantel	PVC, matt
Außendurchmesser	6,5 mm
Min. Biegeradius	35 mm
Betriebstemperatur	-20 °C / +70 °C
Leiterwiderstand	80 Ω/km
Schirmwiderstand	30 Ω/km
Kapazität	52 pF/m
Wellenwiderstand	110 Ω
Dämpfung [dB/100m]	
1 MHz	2.1
3 MHz	5.2
10 MHz	12.5
Isolationswiderstand	> 10 GΩ x km
Prüfspannung	
Ader/Ader	1200 V
Ader/Schirm	500 V