



Galil 6-CO

6.5-Inch, 2-Way Open-Back Ceiling Speakers

| Speakers



The Galil 6-CO is a pair of two-way open-back 8Ω speakers designed for mounting in the ceiling. The speakers feature a multi-tap power transformer for selecting direct 8Ω (bypassing the transformer) or 70V/100V power settings suitable for array installation

FEATURES

Type - 2-way coaxial round open-back ceiling speaker with infinite baffle design

Woofers - 6.5" polypropylene cone with rubber surround

Tweeter - 0.5" Mylar

Frequency Response - 60Hz to 20kHz

Impedance - 8Ω

Sensitivity - (SPL) 87dB (1W @1m with 1kHz)

Recommended Power - RMS 30W, 80W max

Grill - White baffle aluminum grills

Package - 2 speakers (1 pair), template and user manual

Mounting Bracket (Optional) - SKIC-6



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|------------------------------|---|
| DESCRIPTION: | 2-way open-back ceiling speakers |
| HIGH FREQUENCY DRIVER: | 0.5" Mylar dome tweeter |
| LOW FREQUENCY DRIVER: | 6.5" polypropylene cone with rubber surround woofer |
| IMPEDANCE: | 8 Ω |
| DISPERSION COVERAGE: | 120° @2kHz |
| CROSSOVER FREQUENCY: | 3kHz |
| NOMINAL SENSITIVITY: | 87dB SPL @1m, 1W |
| COVERAGE ANGLE: | 104° |
| DIRECTIVITY FACTOR (Q): | 8.5 (averaged 100Hz to 10kHz) |
| DIRECTIVITY INDEX (DI): | 9.2dB (averaged 100Hz to 10kHz) |
| FREQUENCY RESPONSE: | 60Hz to 20kHz |
| INPUT POWER: | 30W RMS, 80W continuous program |
| TRANSFORMER: | 70V – 3.7W/7.5W/15W/30W; 100V – 7.5W/15W/30W |
| RECOMMENDED AMPLIFIER POWER: | 30W |
| INPUT CONNECTOR: | Spring-type push terminal block |
| WEIGHT PER SINGLE SPEAKER: | 1.55kg (3.41lbs) approx |
| SHIPPING WEIGHT (FOR PAIR): | 4.05kg (8.91lbs) approx |
| DIMENSIONS (OD): | 23cm (9.06") |
| CUTOUT DIAMETER: | 19.5cm (7.68") |
| MOUNT DEPTH: | 7.5cm (2.95") |
| OPTIONAL: | SKIC-6 installation bracket |