



Descriptions

The T-6203S is an voice alarm panel especially suitable for small voice alarm system. It will broadcast voice message to help evacuate in all zones over music system.

It is designed with one pair of EMC (Fire alarm activation signal) screw inputs to receive and activate the voice message alarm system over background music system.

The built-in siren is used to automatic broadcast after activation, while the prerecorded voice message also could be recorded and stored through the built-in mic and recorder.

The recording of voice massage could last more than 2 minutes. Play message, play siren, recording through mic or line four locators knob. The alarm mode, play/start, record/stop functional buttons. An output level indicator is provided.

Alarm output for other relative fire alarm equipments.

Fonturo

- * Built-in siren or pre-recorded voice alarm
- * All zone voice alarm panel and voice generator
- * Built-in recorded for user recording 2 minutes voice message
- * 2 ways of recording through mic or line
- * A mic input and a line input are provided for both ways of recording
- * Alarm output for other fire alarm equipments
- * 2 alarm modes: Siren or pre-recorded voice alarm

Specifications	
Model	T-6203S
Indicators	Power LED/Alarm work of the police state of indicator
Power Supply	~110V/60Hz or ~230V/50Hz
Power Consumption	30W
Dimension	484×380×88mm
Weight	4Kg

Connections

