W00FER **8MB600**

Professional Midrange Driver



Key Features

- 2" Voice Coil
- 300 Watts Continuous Power Handling
- 95 dB Sensitivity
- 76-6,000 Hz

GENERAL SPECIFICATIONS		
Nominal Diameter	8.25/209	in/mm
Nominal Impedance	8	ohms
RMS Power	300	Watts
Musical Program Power	600	Watts
Sensitivity	95	dB
Frequency Response	76-6,000	Hz
Voice Coil Diameter	2/50	in/mm
Voice Coil Wire Material	Copper	
Voice Coil Former Material	Kapton®	
	-	


THIELE-SMALL PARAME	TERS		
Equivalent Volume	Vas	9.5	L
Excursion	Xmax	6	mm
Free Air Resonance	Fs	76.71	Hz
Mechanical Factor	Qms	9.13	_
Electrical Factor	Qes	0.54	
Total Factor	Qts	0.51	
Cone Area	Sd	211.5	Cm ²
Mechanical Mass	Mms	29.09	g
BI Factor	BL	11.13	Tm
DC Resistance	Re	4.7	ohms

MOUNTING AND WEIGHT INFORMATION	N	
Overall Diameter ¹	8.25/209	in/mm
Front Mount Baffle Cutout	7.24/184	in/mm
Mounting Depth	3.1/79	in/mm
Overall Depth	3.4/86	in/mm
Net Weight	7/3.175	Lbs/Kgs
Shipping Weight	8.2/3.71	Lbs/Kgs
Carton Dimensions 10 x 10 x 5 /254 x 254 x 127		in/mm

¹Measured at the flat edges. At round edges, 9.4in/239mm

PRV AUDIO USA (USA and Export) MIAMI, FL support@prvaudio.com http://www.prvaudio.com PRV AUDIO BRAZIL (Brazilian Sales Only) SAO LEOPOLDO, RS vendas@pvaudio.com.br http://pvaudio.com.br





209mm / 8.25in

